

## Platform

2.50 m X 6.50 m Platform (9.60 m extended)  
 Single hydraulic powered deck extension  
 Composite treated wooden floor  
 Fold-down/drop-down handrails  
 Self-closing gate  
 Removable platform console box  
 Platform console function status LED's<sup>1</sup>  
 Lanyard attach points  
 Proportional drive control  
 Load sensing system  
 Two speed drive selection  
 Hydraulic differential lock

## Functional Equipment & Accessories

Nivolux self-levelling hydraulic jacks  
 450/70 R20 foam filled lug tread tyres  
 Oscillating rear axle  
 3 degree tilt indicator light with cut-out  
 Ground control selector switch with key lock  
 Full grease lubrication on all scissor arm bushings  
 Manual descent system  
 Hour meter  
 Horn  
 Travel alarm  
 Lifting/tie down lugs

## Available Options

AC cable to platform

## Power & Transmission

Deutz TD2011L04i (50 kW) diesel engine  
 Gull wing steel engine / valve compartment hoods  
 Engine monitoring system with integral shut-down  
 Hydraulic transmission  
 Four wheel drive  
 Drive disconnect/brake release

<sup>1</sup> Indicator LED lights on platform control console for tilt, high drive, lift, drive and overload interlocks.

## 260-25

A. Platform height - elevated	26.00 m
B. Platform height - lowered	3.10 m
C. Platform railing height	1.10 m
D. Stowed height (rails folded)	3.20 m
E. Platform size	2.50 m x 6.50 m
F. Platform length fully extended	9.60 m
G. Overall width	2.50 m
H. Overall length	6.88 m
I. Wheelbase	4.75 m
Ground clearance	0.18 m
Platform capacity	1,000 kg
Capacity on deck extension	1,000 kg
Lift/lower time	100 / 100 sec
Maximum drive height	26.00 m
Deck extension	Hydraulic
Machine weight <sup>1</sup>	24,700 kg
Maximum ground bearing pressure	7.0 kg/cm <sup>2</sup>
Drive speed - high	3.6 km/h
Drive speed - elevated	0.3 km/h
Gradeability (4WD)	25%
Turning radius - inside	1.50 m
Turning radius - outside	7.00 m
Axle oscillation	0.13 m (±)
Tyres	450/70 R80 Foam Filled
Diesel engine	50 kW Deutz TD2011 L04i
Fuel tank capacity	90 L
Hydraulic system	440 L

<sup>1</sup> Certain options or country standards may increase weight and/or dimensions.

