

Platform

2.50 m X 6.50 m Platform (9.60 m extended)

Single hydraulic powered deck extension

Composite treated wooden floor

Fold-down/drop-down handrails

Self-closing gate

Removable platform console box

Platform console function status LED's¹

Lanyard attach points

Proportional drive control

Load sensing system

Two speed drive selection

Hydraulic differential lock

Functional Equipment & Accessories

Nivolux self-levelling hydraulic jacks

450/70 R20 foam filled lug tread tyres

Oscillating rear axle

3 degree tilt indicator light with cut-out

Ground control selector switch with key lock

Full grease lubrication on all scissor arm bushings

Manual descent system

Hour meter

Horn

Travel alarm

Lifting/tie down lugs

Available Options

AC cable to platform

Power & Transmission

Deutz TD2011L04i (50 kW) diesel engine

Gull wing steel engine / valve compartment hoods

Engine monitoring system with integral shut-down

Hydraulic transmission

Four wheel drive

Drive disconnect/brake release

¹ Indicator LED lights on platform control console for tilt, high drive, lift, drive and overload interlocks.

260-25

A. Platform height - elevated	26.00 m
B. Platform height - lowered	3.10 m
C. Platform railing height	1.10 m
D. Stowed height (rails folded)	3.20 m
E. Platform size	2.50 m x 6.50 m
F. Platform length fully extended	9.60 m
G. Overall width	2.50 m
H. Overall length	6.88 m
I. Wheelbase	4.75 m
Ground clearance	0.18 m
Platform capacity	1,000 kg
Capacity on deck extension	1,000 kg
Lift/lower time	100 / 100 sec
Maximum drive height	26.00 m
Deck extension	Hydraulic
Machine weight ¹	24,700 kg
Maximum ground bearing pressure	7.0 kg/cm ²
Drive speed - high	3.6 km/h
Drive speed - elevated	0.3 km/h
Gradeability (4WD)	25%
Turning radius - inside	1.50 m
Turning radius - outside	7.00 m
Axle oscillation	0.13 m (±)
Tyres	450/70 R80 Foam Filled
Diesel engine	50 kW Deutz TD2011 L04i
Fuel tank capacity	90 L
Hydraulic system	440 L

¹ Certain options or country standards may increase weight and/or dimensions.

