

BIBI

CRAWLER SELF-LEVELLING SCISSOR LIFT



850-BL



ALMACRAWLER



HONEST, RELIABLE & REACTIVE
SOLUTIONS FOR WORKING AT HEIGHT



CONTACT US

0800 865 4455
info@hiresafesolutions.com
www.hiresafesolutions.com



Technical data **850-BL** Dati tecnici

Basket capacity	250 kg (2 op.)	Portata in navicella
Basket size	1.50 x 0.78 m	Dimensione navicella
Max working height	7.9 m	Altezza max di lavoro
Max height basket floor	5.9 m	Altezza max calpestio
Moving height	6.0 m	Altezza di traslazione
Accelerator	Automatic	Acceleratore
Undercarriage	Bi-Levelling	Sottocarro
Basket levelling	Automatic	Livellamento navicella
Longitudinal levelling Front	+/- 16°	Livell. longitudinale anteriore
Longitudinal levelling Rear	+/- 20°	Livell. longitudinale posteriore
Lateral levelling	+/- 15°	Livell. laterale
Electric pump (option)	220V-2,2kW	Elettropompa (opzionale)
Direction-Control System	Yes	Direction-Control System
Easy-Drive System	Yes	Easy-Drive System
Max speed	max 2.20 km/h	Velocità massima
Ground emergency	Yes	Comandi di emergenza a terra
Control of inclination	Automatic	Controllo dell'inclinazione
Gradeability	25°	Pendenza superabile
Side slope	21°	Massima pendenza laterale
Length	1.94 m	Lunghezza
Width	1.30 ÷ 1.50 m	Larghezza
Min height with narrow tracks (folded railings)	2.28 (1,98) m	Altezza minima ringhiere ripiegate con cingoli stretti
Min height with wide tracks (folded railings)	1.98 (1,68) m	Altezza minima ringhiere ripiegate con cingoli larghi
Compliance	EN 280, ANSI, CSA, AS/NZS	Conforme

Version

BL		Gasoline Honda iGX390	Gasoline Honda iGX390	Gasoline Honda iGX390	BL
	-	Diesel Hatz 1B40	Diesel Hatz 1B40	Diesel Hatz 1B40	-
		2070 kg / 2090 kg	2500 kg / 2530 kg	2860 kg / 2890 kg	

Versione

BIBI 850-BL

