

Electric Drive Scissor Lifts


22m



4WS



Great Passability



Ultra-long Platform



Self-leveling Hydraulic Outriggers

Model: JCPT2212DC

The maximum working height is 22m, the heavy load at full height is 600kg, the whole machine adopts pure electric drive, has 4WS&4WD ability, turning radius is 0.5m/2.5m, can be crab-steering. In addition, the JCPT2212DC is equipped with a 4.3m×1.19m working platform and a 1.8m long extended platform, with a wider operating range.

Different from the 22m JCPT2223DC, JCPT2212DC width is only 1.25m, with excellent passability, can easily go through the narrow doorframes, channels, etc. In view of pure electric drive, JCPT2212DC has no pollution, zero emission, energy saving and environmental protection, suitable for indoor and outdoor working environment with high environmental requirements.

Standard Equipment

Proportional controls / Automatic pothole protection / Self-lock gate on platform / Automatic leveling hydraulic outriggers / Non marking tyre / 2WD / Automatic brakes system / Emergency stop button / Emergency lowering system / Cylinder holding valve / Onboard diagnostic system / Tilt sensor with alarm / All Motion Alarm / Horn / Hour meter / Safety brackets / Folding guardrails / Extended platform / Charger protection / Flashing beacon

Options

Overload sensor with alarm / AC power on the platform / Platrom work lights / Airline to the platform

Model	JCPT2212
Drive Type	= Electric = Engine DC

Size	
MAX.Working Height	22.00m
MAX.Platform Floor Height	20.00m
Overall Length	4.72m
Overall Width	1.25m
Overall Height(Rails Up)	3.82m
Overall Height(Rails Down)	2.99m
Platform Size(Length/Width)	4.30×1.19m
Platform Extension Size	1.80m
Ground Clearance	0.20m
Wheelbase	3.18m
Turning Radius(Inside/Outside)	0.5m/2.5m
Tyre Size	28×10-22

Performance	
Capacity	600kg
Capacity On Extension	600kg
Max.Occupants	2
Gradeability	25%
Travel Speed(Stowed)	3.0km/h
Travel Speed(Raised)	0.5km/h
MAX. Working Slope	1°(0°)
Up/Down Speed	80/100sec

Weight	
Overall Weight	12350kg

Power	
Hydraulic Tank	130L
Batteries	48V/630Ah
Integrated Charger	48V/60A
Drive Motor	4×AC 32V/3.3kW
Lifting Motor	2×DC 48V/8.0kW