SPECIFICATIONS

Size	Metric	British
Max. Working Height Ⓐ	28.00m	91ft 10in
Max. Platform Height Ⓑ	26.00m	85ft 4in
Overall Length Ⓒ	5.96m	19ft 7in
Overall Width Ⓓ	2.50m	8ft 2in
Overall Height(Rails Up) Ⓔ	4.13m	13ft 7in
Overall Height(Rails Down) Ⓕ	3.19m	10ft 6in
Platform Size(Length×Width)	5.48m×2.45m	18ft×8ft
Platform Extension Size Ⓖ	2.10m	6ft 11in
Ground Clearance	0.23m	9in
Wheelbase Ⓗ	4.10m	13ft 5in
Turning Radius(Inside/Outside)	3.50m/6.00m	11ft 6in/19ft 8in
Tyres	355/55D625	355/55D625

Performance		
S.W.L	1000kg	2204lb
S.W.L On Extension	1000kg	2204lb
Max. Occupants (Indoor/Outdoor)	4/4	4/4
Gradeability	40%	40%
Travel Speed(Stowed)	4.0km/h	2.49mph
Travel Speed(Raised)	0.3km/h	0.19mph
Max. Working Slope	X-2°/Y-3°	X-2°/Y-3°
Up/Down Speed	110/100sec	110/100sec

Weight		
Overall Weight	19800kg	43651lb

Power		
Diesel Engine	55kW/2600rpm	55kW/2600rpm
Diesel Tank	130L	34gal
Hydraulic Tank	260L	69gal

ENGINE

HireSafe SOLUTIONS

HONEST, RELIABLE & REACTIVE
SOLUTIONS FOR WORKING AT HEIGHT

CONTACT US
0800 865 4455
info@hiresafesolutions.com
www.hiresafesolutions.com

FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- Automatic One-Way Platform Extension Deck
- Four-Wheel Drive
- Four-Wheel Steering
- Automatic Braking System
- Self-Weight Lowering System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Hydraulic Oil Cooling System
- Flashing LED Beacon
- Foldable Guard Rails
- Drive Enable
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Automatic Leveling Hydraulic Outriggers
- Anti-Restart Engine Protection
- Emergency Pump
- Emergency Stop Button
- Platform Load Sense System
- Drivable At Full Height

HireSafe SOLUTIONS

HONEST, RELIABLE & REACTIVE
SOLUTIONS FOR WORKING AT HEIGHT

CONTACT US
📞 0800 865 4455
✉ info@hiresafesolutions.com
🌐 www.hiresafesolutions.com