



# Model 4045R SCISSOR LIFTS

## Performance

• Working Height	13.96 m
- Platform Height - Elevated	11.96m
B. Platform Height - Lowered	1.4m
C. Platform Railing Height	1.13m
- Stowed Height (Rails Folded)	1.92m
E. Platform Size Inside (W x L)	1.05m x 2.43m
F. Deck Extension	0.91m
G. Overall Width	1.14m
H. Overall Length	2.71m (3**)
I. Wheelbase	2.03m
J. Ground Clearance (centre of machine)	12,6cm
• Platform Capacity (1)	350kg (4)
• Capacity on Deck Extension	113kg
• Lift/Lower Time ( no load )	68/41 sec.
• Maximum Drive Height	8.74m
• Machine weight (2)	3,175 kg
• Maximum Ground Bearing Pressure	9,00 kg/cm <sup>2</sup>
• Drive Speed - Lowered	3.22 km/h
• Drive Speed - Elevated	0.8 km/h
• Gradeability	25%
• Turning Radius - Inside	0.0m
• Turning Radius - Outside	2.54m
• Tyres (Non-Marking Solid)	406 x 127
• Brakes	Hydraulic
• Drive (Nominal)	Hydraulic
• Batteries	4x 12V 150A/hr
• Charger (120/240V -50/60Hz)	24v @27Amp Automatic
• Pump Motor	4.5kW
• Hydraulic System	30L



- 1 Capacities shown are maximum with 2 persons indoor on both models.  
Outdoor rating 1 person/250kg
- 2 Certain options or country standards may increase weight and/or dimensions.
- 3\*\* includes ladder, excluding ladder 2,56m
- 4 indoor, 250kg outdoor
- 5 indoor, 125kg outdoor

## Dimensions

